

Universal Shaker SM 30 C



Description

Table-top shaker for high loads and continuous operation

Basic Equipment

Basic device with shaking plate and rubber mat, **without rack system**

Loading Capacity

Erlenmeyer flasks	100 ml	42 pieces
Erlenmeyer flasks	250 / 300 ml	20 pieces
Separating funnels	250 ml	6 pieces
Separating funnels	1000 ml	4 pieces
Test tube racks		5 pieces

Details

Motion:	can be switched from orbital to reciprocating
Shaking platform:	560 x 400 mm
Max. load:	30 kg
Shaking speed:	15 - 300 rpm, steplessly adjustable
Stroke:	26 mm
Runtime:	0 - 120 min / continuous
Order No.:	6105 000

Accessory: Rack System Combifix SM A
Rack System Combifix SM B
Rack System Combifix SM C
Universal tray SM
2-storey top frame SM
Incubator Hood TH 30

Technical specifications

Electrical supply: 230 V or 115 V, 50 / 60 Hz please indicate in case of order
Enclosure protection: IP 21
Heat emission: approx 20 W
Ambient temperature: 5°C to 50°C
Relative humidity: ~ 85 %
Dimensions (w x d x h): 680 x 610 x 160 mm
Weight: 33 kg